


# AS-200 SPECTRALSHIELD™

## SOUND AND VIBRATION PRODUCTION LINE TEST SYSTEM



**SpectralShield™** is designed to characterize the physical properties of manufactured products. It can reduce warranty costs by identifying defective products. This system can grade products directly on the production line, allowing products to be sold later by quality level. It provides quality metrics documentation, a key factor in improving manufacturing practices. **SpectralShield™** is an essential tool that monitors the manufacturing process, increases yields, and tightens product tolerances.

Most sensors that produce an analog signal can be connected to the **SpectralShield™** system. Flexible signal conditioning provides programmable gain, anti-alias filtering, overload protection, AC/DC coupling, and IEPE transducer power. The system supports a wide range of sensors including accelerometers, displacement sensors, pressure transducers, proximity probes, thermocouples, flow meters, and strain gauges.

Operators can easily configure tests by defining the acceptable time, frequency, and statistical limits for a product. Once configured, the system can detect transient events (spikes or glitches) and frequency components (unbalance, shaft misalignment, or defective bearings).

**SpectralShield™** can be configured not only to measure the tested part, but also the test stand and surrounding environment. These other measurements enable the operator to both recognize and modify the external influences that cause part failure.

**SpectralShield™** can run as a stand-alone system or with limited operator interaction. Data acquisition can be triggered by an operator, external relay, industrial computer, or control system. The system will acquire and process the incoming signals, then compare them against good product signatures and indicate if the part passed or failed.

# AS-200 SPECTRALSHIELD™

SOUND AND VIBRATION PRODUCTION LINE TEST SYSTEM

## CHANNEL DISPLAY

### SPECTRUM PLOT

Live, Average, Peakhold, Integration/Differentiation

### SPECTRUM CRITERIA

Overall Amplitude, Window, Energy Band, Phase, Envelope, and Total Harmonic Distortion

### TIME PLOT


Time Signature

### TRANSFER FUNCTION CRITERIA

Magnitude, Phase, and Coherence

### ADVANCED CRITERIA

Hilbert Envelope, Sound Pressure Level, Speed, and Wavelet



### MARKER TABLE

Marker #, Frequency, and Value

### DATA MARKERS

Peak, Harmonic, Sideband, Order, Delta Frequency, Delta Time, and User Defined

### TIME CRITERIA

Threshold, Trigger, Crossing, and Crest Factor



### STATISTICAL CRITERIA

Mean, Sigma, Skew, and Kurtosis


## COMPONENT TESTING



## IMPACT TESTING



Real-time Acquisition and Analysis with Multiple Test Criteria



Transfer Function Magnitude, Phase, Real, Imaginary, and Coherence

# AS-200 SPECTRALSHIELD™

SOUND AND VIBRATION PRODUCTION LINE TEST SYSTEM





### SENSOR SIGNALS

Accelerometers, Proximity Probes, Vibrometers, Pressure Transducers, Velocity Probes, and Tachometers



### CONTROL DEVICES

PLC and DCS, Network Sockets, Digital Inputs, RS-232, Ethernet, and Barcode Readers



### REPORT GENERATION

Test Log, HTML Reports, E-mail, Spreadsheets, Time and Spectrum Blocks, and Trending



### OUTPUT DEVICES

Electromechanical Relays, PLC and DCS, Ethernet, RS-232, and Printers



### DATA EXPORT

ASCII, Mathwork's Matlab, WAV, SQL, Vibrant's MEScope, and UFF (Universal File Format)

Contact Alta Solutions for the latest specifications and ordering information.



### Alta Solutions Incorporated

12580 Stowe Drive Poway, CA 92064, USA

Toll-Free Phone: (877) 258-2765

Email: sales@altasol.com, Web Site: www.altasol.com